

F502 Fanfold Color Label Printer

Rugged Construction Meets Versatile Printing

The F502 is a small-footprint fanfold label printer, capable of producing durable, full-color labels on-demand. All-steel industrial design, improved toolbox functionality, over 2x faster printing, and optional durable pigment inks make the F502 extremely rugged and versatile.

The heavy-duty construction of the F502 color label printer includes a steel body with a window for print bed visibility and status monitoring. Improved sensors allow for greater compatibility with specialty media, such as reflective metallic material.

The F502's pigment inks have been tested and **certified to produce BS 5609-compliant and GHS (Globally Harmonized System) labels**, which helps keep chemical manufacturers in compliance with packaging and transportation requirements.

Key Features

- ✓ Pigment inks provide exceptional water, abrasion, and UV resistance
- ✓ Print vibrant and colorful prime labels with dye-based inks
- ✓ Industrial steel construction
- ✓ Flexibility to change label designs and content on the fly
- ✓ Best for short- to mid-sized print runs



afinialabel.com

US Office
sales@afinialabel.com
+1 888.215.3966



UK Office
sales@afinia.co.uk
+44 (0) 845.250.7949



AFINIA LABEL®

F502 Specifications

General:

Print Technology:	HP Thermal Inkjet
Print Resolution:	Up to 4800 dpi
Print Speed:	Approximately 5.2 in/sec (13.2 cm/sec) printing a 2.2 in (56 mm) wide image in plain paper normal mode
Inks:	Option of Dye or Pigment — Individual Cyan, Magenta, Yellow (26 mL), Individual Black (78.4 mL)
Media Format:	Fanfold
Media Types:	Compatible with wide range of paper, polyester, polypropylene, and vinyl label stocks. Supports gap, black mark, and continuous media
Media Sensing:	Auto calibration and auto detection of gap and black marks
Label Width:	1.0" – 8.5" (25.4 mm – 215.9 mm)
Label Length:	0.75" – 48" (19 mm – 1219.2 mm)
Media/Liner Width:	1.5" - 8.65" (38.1 mm – 219.7 mm)
Inter Label Gap Size:	0.125" – 0.3" (3.175 mm – 7.62 mm)
Black Mark Size:	0.125" – 0.3"
Label Thickness:	0.004" – 0.01" (0.1 mm – 0.3 mm)
Cutter:	Powered cutter
Display:	2" mono display with buttons
Operating Systems:	Windows 10/11, 64-bit, Intel/AMD x86/x64 only. ARM/Snapdragon not supported
Data Interface:	USB 2.0 connection and 10/100 Base-Tx Ethernet
Operating Temperature:	59 – 90°F (15 – 32°C)
Operating Humidity:	20 – 80% RH
Overall Dimensions:	20" (511 mm) W, 23.5" (596 mm) D, 9.75" (248 mm) H
Weight:	40 lb (18.2kg)
Warranty:	1 year



DURABLE LABELS

Use pigment-based inks for maximum durability



Waterproof



Abrasion Resistant



UV Resistant

PRIME LABELS

Use dye-based inks for vibrancy and "pop"



Vibrant Color



Optimal Contrast



Eye Catching



afinialabel.com

US Office
sales@afinialabel.com
+1 888.215.3966



UK Office
sales@afinia.co.uk
+44 (0) 845.250.7949

AFINIA LABEL