

## Accessories for the LT5C

### Optimize your label printing workflow

Designed specifically for the LT5C, these accessories provide options for improved workflow and efficiency. Industrial design and heavy-duty construction makes these items perfect for high volume jobs.



### Label Rewinder


Rewind printed output from your LT5C onto 3-inch cores. Speed is automatically synchronized by the tension arm and alignment is maintained by a steel connection plate for tight, consistent rolls.



### Inline Slitter\*/Matrix Remover

Create perfect edge-to-edge (full bleed) labels by printing over the cut edge of pre-die-cut labels. Removing the waste matrix in as the labels exit the printer provides optimal efficiency. A connection plate and tension arm ensures roll tightness and consistency.

*\*Available without slitting module.*



### Slitter/Matrix Remover

This offline rewinder is perfect full bleed labels that need to be slit down to separate narrow rolls. Printed rolls are placed here for waste matrix removal and slitting. Slitting blade positions are easily adjusted for accurate and tight finished rolls.

[afinialabel.com](http://afinialabel.com)

**US Office**  
[sales@afinialabel.com](mailto:sales@afinialabel.com)  
+1 888.215.3966



**UK Office**  
[sales@afinia.co.uk](mailto:sales@afinia.co.uk)  
+44 (0) 845.250.7949

**AFINIA LABEL®**

# LT5C Accessories Specifications

## LT5C Label Rewinder:

<b>Outer roll diameter:</b>	Up to 9.84 inches (250 mm)
<b>Media width:</b>	Up to 6.7 inches (170 mm)
<b>Core holder :</b>	3 inch (76 mm)
<b>Power supply:</b>	External auto-switching 100/240VAC - 2.5A at 24V




## LT5C Inline Slitter/Matrix Remover:

<b>Outer roll diameter:</b>	Up to 9.84 inches (250 mm)
<b>Media width:</b>	Up to 6.7 inches (170 mm)
<b>Core holder :</b>	3 inch (76 mm)
<b>Power supply:</b>	External auto-switching 100/240VAC - 2.5A at 24V
<b>Slitter blades :</b>	Up to 6 (3 blades included)
<b>Minimum slitting width:</b>	0.75 inches (19 mm)



## LT5C Slitter/Matrix Remover (Offline):

<b>Outer roll diameter:</b>	Up to 7.87 inches (200 mm)
<b>Media width:</b>	Up to 6.7 inches (170 mm)
<b>Core holder :</b>	3 inch (76 mm)
<b>Power supply:</b>	External auto-switching 100/240VAC - 2.5A at 24V
<b>Slitter blades :</b>	Up to 6 (3 blades included)
<b>Minimum slitting width:</b>	0.75 inches (19 mm)



[afinialabel.com](http://afinialabel.com)

**US Office**  
sales@afinialabel.com  
+1 888.215.3966



**UK Office**  
sales@afinia.co.uk  
+44 (0) 845.250.7949

**AFINIA LABEL**